



## SC14 回转驱动性能参数

### Slewing Drive Performance Parameters

减速比	Gear Ratio	85:1	
输出转速	Output Speed	0.018rpm	
输出力矩	Output Torque	10200N.m	7527 lbf.ft
最大倾覆力矩	Tilting Moment (max.)	67.8KN.m	50×10 <sup>3</sup> lbf.ft
保持力矩	Holding Torque	48 kN.m	42×10 <sup>3</sup> lbf.ft
轴向静载荷	Static Axial Load Rating	555 kN	124.9×10 <sup>3</sup> lbf
径向静载荷	Static Radial Load Rating	222 kN	49.9×10 <sup>3</sup> lbf
机械效率	Mechanical Efficiency	40%	
自锁性	Self-locking	可靠的静态自锁Reliable static self-locking	
精度	Precision	≤0.2°	
防护等级	IP Class	IP65	

## VH14 回转驱动性能参数

### Slewing Drive Performance Parameters

减速比	Gear Ratio	85:1	
输出转速	Output Speed	0.018rpm	
输出力矩	Output Torque	10200N.m	7527 lbf.ft
最大倾覆力矩	Tilting Moment (max.)	67.8KN.m	50×10 <sup>3</sup> lbf.ft
保持力矩	Holding Torque	48 kN.m	42×10 <sup>3</sup> lbf.ft
轴向静载荷	Static Axial Load Rating	555 kN	124.9×10 <sup>3</sup> lbf
径向静载荷	Static Radial Load Rating	222 kN	49.9×10 <sup>3</sup> lbf
机械效率	Mechanical Efficiency	40%	
自锁性	Self-locking	可靠的静态自锁Reliable static self-locking	
精度	Precision	≤0.2°	
防护等级	IP Class	IP65	